



# VP300 The Cutting-edge Pin Pad Technology

Optimize your payment operations using the VP300, a high-performance, all-inclusive solution with a competitive edge.

#### **User-friendly and Intuitive Experience**

Indulge in a user-friendly encounter with our spacious touchscreen display and exclusive stylus on our intuitive interface. Explore the digital signature capture function that enriches the overall user experience.

#### **Customer Feedback & Satisfaction**

Utilize our integrated built-in customer feedback rating system for insights to refine services and increase customer satisfaction. Elevate your service excellence, one feedback survey at a time.

#### **Enhanced Payment Security**

Provide your customers heightened security features with our enhanced pin pad technology, providing an extra layer of protection during the PIN entry process. The PCI-PTS 5.0 ensures customer security.

#### **Secure and Convenient Contactless Payments**

Embrace the future of payments with advanced EMV technology, ensuring utmost security for transactions. Choose from swipe, tap, and dip card payment options, accompanied by a secure digital signature capture feature, making payments both safe and convenient.

### **Features**



Touchscreen Display



Included Stylus



EMV



Digital Signature Capture



PCI-PTS 5.0 Certified Pin Pad

## **Specifications**



OS		Proprietary
CPU		32-bit high performance secure processor
Memory		32MB RAM, 64 MB Flash
Display		2.4-inch TFT full color LCD display, resolution of 320 x 240
Card Reader	Magnetic Card	Triple track, bi-directional, conforming to ISO 7810/7811/7813
	Smart Card	EMV L1/L2, conforming to ISO 7816, 1.8V/3V/5V, synchronous & asynchronous, T=0 & T=1
	Contactless	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica
Audio		Built-in buzzer
Keypad		10 x alphanumeric keys, 9 x function keys
Peripheral Ports		1 x RS232 (RJ11) or 1 x USB
Power Supply		5.0V DC, 1.0A
Dimensions (mm)		141(L) x 71(W) x 36(H)
Weight		160g
Environment	Operating temperature	0°C ~ 40°C (32°F ~ 104°F)
	Storage temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Relative humidity	5% ~ 93% (Non-condensing)
Certifications		PCI PTS 5.x, EMV L1/L2, EMV EMV Contactless L1, PayPass, payWave, American ExpressPay, Discover D-PAS, UnionPay QuickPass, TQM, CE, RoHS







